



JT-053S


Smart Security Fog Generator Feature:

- Full 360-degree infrared sensor night vision coverage monitoring no dead Angle.
- PIR Detection 360 degree coverage your monitor area without dead Angle.
- Independently developed 3PCS fog formula containers are easily replaced by "buckle" push-press mode, fog vent size upto 12MM.
- Alarm call notification,platform information push, monitor platform unique code verification guaranteed fog triggered zero false alarm.
- Support multiple generic wireless alarm detector seamless connection on the market such as door magnet, IR sensor.
- APP control easy to operate, panorama 3.6MP image quality,high definition clear picture, fast and smooth transmission,double backup of alarm video, one key download alarm video, multiple channels to find video alarm: custom time search, alarm sensor search, alarm push search.
- Elegant and compact appearance adopts the "3U" large enclosure design with strong three-dimensional sense.


SPECIFICATION

Name	Model:	JT-053S	Network	Smart Alarm	Motion detection
	Name	Security Fog Generator with 3MP 1/2.8" CMO Network Camera		A key configuration	Find IP via access outer net
Camera	Image Sensor:	1/2.8" Ppogressive scan CMOS	Interface	General Function:	Anti-Flicker, heartbeat, mirror password protection
	Min. Illumination:	0.02Lux@ (F2.0, AGC ON) 0Lux with IR		Storage Interface	Micro SD CARD (MAX 128G)
	Shutter time:	1/3 s to 1/100,000 s		Power Interface	Micro USB interface
	Lens	4mm@ F2.2		Communication Interface	1 RJ45, 10/100M
	Lens mount	M12 Support 2.4mm, 4mm 6mm, 8mm Lens	Wi-Fi Specification	Wireless Standards	IEEE802.11b, 802.11g
	Day& Night:	ICR Infrared filter type with auto switch		Frequency Range:	2.1GHHZ~2.4835GHZ
	Digital noise reduction:	3D DNR		Channel Bandwidth:	Support 20MHZ
	Wide Dynamic Range:	Digital WDR		Security	64/128-bit WEP, WPA/WPA2 WPA-PSK/WPA2-PSK
Compression Standard	Motion Detection	on/off/ sensitivity adjustment	Alarm	Transmission Rate:	11b : 11Mbps, 11g : 54Mbps
	Video Compression	H.264		RF alarm frequency	868.4MHZ EU, 908.4MHZ US 921.4MHZ ANZ, 869.2MHZ RU
	H.264 code profile:	Main Profile		RF Distance	Indoor 50m, outdoor 100m
	Video bit rate:	Ultra clear, hd, balanced process		Support Alarm Sensor	Support door magnet and PIR alarm
Image	Max. Image Resolution:	1920x1080@30fps 720x480@30fps 360x240@30fps capturing : 2048*1536 JPG support main stream and sub stream separately	General	GPIO	1 GPIO
	Frame Rate	50 Hz: 25 fps (1280 x 960), 25 fps (1280 x 720)		PIR*3PCS	Built-in 3PCS PIR sensor layout
	Image Settings	Saturation, Brightness, Contrast adjustable by client software or web browser		Operating Conditions:	Less than 90% RH/-10° C ~ +45° C
	backlight compensation	support		Power Supply:	12V@5A
				IR Range:	10 m to 15 m
				Dimensions (mm) :	230*230*60mm

Model:JT-053S Color Available



Multiple Startup Mode



Jingtai Fog Generator can be triggered by **POWER 12V/4A**

- 1.Manual activate ,triggered by panic button.
- 2.Manual remote control,triggered by Internet monitoring center system.
- 3.Automatic activate,triggered by controller,sensor,alarm etc.